# LIFE CYCLE ASSESSMENT OF EMERGING PROCESSES TO VALORIZE MINING WASTE

#### Lugas Raka ADRIANTO<sup>1</sup>, He NIU<sup>2</sup>, Stephan PFISTER<sup>1</sup>

<sup>1</sup> ETH Zurich, Chair for Ecological System Design, Department of Civil and Environmental Engineering, 8093, Zurich, Switzerland

<sup>2</sup> University of Oulu, Fibre and Particle Engineering Research Unit, 90570, Oulu, Finland

adrianto@ifu.baug.ethz.ch, he.niu@oulu.fi, stephan.pfister@ifu.baug.ethz.ch

## Introduction

The notion of transforming waste as secondary resources for substituting materials in the current economy is getting more popular<sup>1</sup>. Besides limiting environmental consequences<sup>2</sup>, copper mining residues such as waste rock has been viewed as one of the promising materials for valorisation due to its resource availability. A particular product such as alternative cementitious binders can be made out of this waste, after which the raw waste undergoes treatment processes to achieve the desired mechanical properties. Attempts to replace ordinary Portland cement require an array of mechanochemical activation methods<sup>3</sup> to the original waste, thereby leveraging the values of original materials. While the concept of recycling waste may sound beneficial at first, one must showcase the environmental benefits following the life cycle thinking approach including all processes. Various inputs and outputs that come along the novel value chains imply the introduction of resources into the system. Moreover, the maturity and scale of emerging and conventional technologies have shown to be important in the assessment. In this study, we demonstrate the first steps towards understanding the potential for environmental savings through prospective life cycle assessment of geopolymer-based concrete. To account for process changes, we implement upscaling strategies to the life cycle stages of geopolymer production. Analysing this systematically can help us pinpoint environmental bottlenecks and tradeoffs, as well as justifying the benefits of substituting common concrete with a more sustainable material.

# **Materials and Methods**

A life cycle assessment (LCA) was conducted to quantitatively assess environmental impacts of concrete production through three valorisation pathways of waste. This product is intended to substitute standard cement concrete in the market. The five cases developed in Table 1 also serve as comparisons between the novel routes (i.e., geopolymer derived from waste rock) and the conventional one (i.e., Portland cement), in which the latter needs clinker processing. Therefore, we defined the functional unit as the supply of '1 m<sup>3</sup> concrete with 40 MPa mechanical strength'.

Route	S1: Precursor	S2: Binder	S3: Concrete	Data source
Lab scale geopolymer concrete	Jaw crushers and double-roller crushers	Recipes based on own experiments. (Mixing precursors with alkali activators)	Geopolymer concrete mix designs obtained from literature reviews <sup>4</sup>	In-house <sup>3</sup> , expert inputs, process simulation, and calculated inventory
Geopolymer concrete, route 1	Thickener only			
Geopolymer concrete, route 2	Pressure filters with water saving			
Geopolymer	Double sieving with			
concrete, route 3	water saving			
Standard concrete	Portland cement concrete via hi-temperature calcination			ecoinvent 3.6 <sup>5</sup>

**Table 1.** Processes involved to manufacture 1 m<sup>3</sup> concrete, 40 MPa and the data source

The first route comprises inventory data from the performed experiments developed inhouse, which entails the direct measurement at the laboratory<sup>3</sup>. Basing on the first route, we created three upscaled routes that represent the adjusted life cycle inventory data at large scale operation in Europe, next to the mining area. This was done by simulating the step 1 (S1) in a mineral process simulator HSC Sim<sup>6</sup> that entails scale changes, synergies, and efficiency improvement, following frameworks suggested by Tsoy et al<sup>7</sup>. The three different cases were made to examine the effect of altering critical equipment in the precursor grinding configuration and how it will impact the overall results. Meanwhile, the use phase and end of life of concretes manufactured were all excluded in this study. The overall scheme is depicted in Figure 1.

The environmental performances for all cases were calculated for three impact categories, namely 1) climate change, 2) cumulative energy demand, 3) water scarcity footprint (AWARE). This was done to evaluate trade-offs across different categories.



Figure 1. The scheme for geopolymer concrete production

### **Results and Discussion**

The upscaling efforts for three simulated cases in the precursor and the binder making step reduce climate change impacts between 85 - 88% of the original value (see Figure 2, part A). These environmental gains come from two factors. First, the economies of scale play a major role in reducing grinding electricity input in the initial stage. At large scale, high intensity grinding mill is installed to replace lab pulverisers with higher electricity per mass input. This proves that producing geopolymer at commercial scale is not only feasible, but also favourable in terms of climate change and cumulated energy demand. Once the precursor making is assumed to reach the standard industrial throughput (i.e. 100t/h, according to the high intensity grinding mill technical spec<sup>6</sup>), the environmental impact is significantly reduced. The geopolymer concrete emits even lower CO<sub>2</sub> emissions than common cement concrete in the market, as it avoids the high temperature calcination process that is replaced by mechanochemical activation.



Figure 2. Part (A) compares climate change impacts of geopolymer concrete in lab scale and upscaled cases. Part (B) shows the potential savings/ losses compared to ordinary Portland cement concrete (grey bars) across different categories

Second, process synergies in the circuit might reduce water and reagents consumption. For instance, the choice of configurations from route 1 to route 2 and 3 enables water recirculation to be installed and thus minimize tap water intake. This parameter may not affect the results drastically in this study, but when production is planned in regions with high water scarcity, then it would amplify the benefit of one route to another. Even though the recirculation strategy might be worthy for the climate change and cumulative energy demand impact category, it is the opposite for the water scarcity footprint. One may further decrease these impacts by sourcing alkali activators and lithium from side-stream based materials<sup>8</sup> and less resource-consuming productions. However, in most cases, climate change impacts are more important than water scarcity for concrete production.

#### Conclusion

The combined upscaling and life cycle assessment approach are able to detect energy and environmental hotspot and to provide feedback for process designers, especially concerning preparation of alkali activator chemicals from more sustainable alternatives such as sodium carbonate, calcium hydroxide and even underutilized alkaline residues. Different configurations matter in terms of environmental performance when there are open technological routes to upscale bench-scale experiments to industrial ones. Beyond the specific case, this study can be replicated to prospective LCA studies for other mine waste valorisation opportunities<sup>9</sup>. As an outlook, multiple scenarios with different future trajectories<sup>10</sup> and technological routes can create more holistic forwardlooking studies, investigated in terms of ecological benefits and practical applications.

# References

- 1. Edraki, M. *et al.* Designing mine tailings for better environmental, social and economic outcomes: a review of alternative approaches. *J. Clean. Prod.* **84**, 411–420 (2014).
- 2. Lottermoser, B. G. Recycling, Reuse and Rehabilitation of Mine Wastes. *Elements* **7**, 405–410 (2011).
- 3. Niu, H. *et al.* Recycling mica and carbonate-rich mine tailings in alkali-activated composites: A synergy with metakaolin. *Miner. Eng.* **157**, 106535 (2020).
- 4. Hassan, A., Arif, M. & Shariq, M. Use of geopolymer concrete for a cleaner and sustainable environment A review of mechanical properties and microstructure. *Journal of Cleaner Production* **223**, 704–728 (2019).
- 5. Ecoinvent, E. Swiss centre for life cycle inventories. (2019).
- 6. Outotec. HSC Chemistry. (2020). Available at: https://www.outotec.com/products-andservices/technologies/digital-solutions/hsc-chemistry/. (Accessed: 5th June 2020)
- Tsoy, N., Steubing, B., van der Giesen, C. & Guinée, J. Upscaling methods used in ex ante life cycle assessment of emerging technologies: a review. *Int. J. Life Cycle Assess.* 1–13 (2020). doi:10.1007/s11367-020-01796-8
- 8. Adesanya, E. *et al.* Opportunities to improve sustainability of alkali-activated materials: A review of sidestream based activators. *Journal of Cleaner Production* **286**, 125558 (2021).
- 9. SULTAN. Marie Skłodowska -Curie Actions (MSCA ) Innovative Training Networks (ITN ) Annex 1 to the Grant Agreement (Description of the Action ) Part B. *Proj. Propos.* 1–31 (2018).
- 10. Arvidsson, R. *et al.* Environmental Assessment of Emerging Technologies: Recommendations for Prospective LCA. *J. Ind. Ecol.* **22**, 1286–1294 (2018).

This research has received funding from the European Union's EU Framework Programme for Research and Innovation Horizon 2020 under Grant Agreement # 812580